

## Site barracks for the installation of boiler-room with VERNER boiler - technical description -

### IRON FRAME

- welded iron construction from open and rolled profiles with thickness 3mm
- corner cubes according to the ISO norms

### FLOOR

- floor girders with zinc-coated plate with thickness 0,6-0,7mm
- plates from mineral cotton-wool with thickness 80/100mm
- PE - foil
- plywood plate with thickness 22mm /E1/
- PVC with thickness 1,5mm
- maximum load of the floor: 250kg/m<sup>2</sup>

### PERIPHERAL WALLS

- wall girders with zinc-coated moulded plate with thickness 0,6 – 0,75mm
- plates from mineral cotton-wool with thickness 50mm
- double-sided laminated plywood plate with thickness 10mm /E1/
- standardly white decoration, for extra charge also light oak decoration

### ROOF

- roof cover from zinc moulded plate with thickness 0,6 – 0,75mm
- plates from mineral cotton-wool with thickness 100mm
- PE - foil
- double-sided laminated plywood plate with thickness 10mm /E1/
- standardly white decoration
- maximum load of the roof: 150kg/m<sup>2</sup>

### BEHIND-DOOR

- wooden frame without isolation
- without isolation, it is also possible to supply it with mineral cotton-wool with thickness 50mm (for extra charge)
- double-sided laminated plywood plate with thickness 10mm /E1/
- standardly white decoration, for extra charge also light oak decoration

### DOOR

- outside: single-door, zinc-coated, isolated, smooth
- left or right design, dimension 875x1970mm
- inside: single-door, plywood-wood with stuffed comb
- left or right design, dimension 850x1970mm

### WINDOWS

- standardly plastic 900x1200mm, 1800x1200mm with the outside window-blind and safety
- sanitary design 600x600mm with the opaque glass

### WIRING SYSTEM

- according to ČSN or DIN, 400/230V
- CEE outside connecting release and socket 400V/32A/5p
- electric switch-board AP
- FI earth-leakage breaker 40/4E-0,1A
- LS circuit breaker 10A /light/
- LS circuit breaker 16A /sockets/
- sockets, switch
- socket for direct-heating device 2kW
- bath fluorescent tubes 2x36W

### PAINTING

- standard colour tones  
RAL 7035 light grey, RAL 9010 pure white or blue RAL 5010
- other tones RAL according to requirement for extra charge

**Sample photos of the site barrack (container):**



**VERNER a. s.**

Sokolská 321, 549 41 Červený Kostelec,  
telefon: +420 491 465 024, +420 491 462 135

email: [info@verner.cz](mailto:info@verner.cz)

[www.verner.cz](http://www.verner.cz)